

PRODUCT INFORMATION

ESTISOL™ 140

Synthetic ester

Product Description

ESTISOL 140 is an aliphatic synthetic ester with high solvency power.

ESTISOL 140 has a high flash point and a low viscosity.

ESTISOL 140 has a very low surface tension and shows excellent wetting properties.

Industrial Application

ESTISOL 140 is used as a solvent in industrial cleaners, coatings, adhesives and other formulated chemical products.

ESTISOL 140 may be applied as an alternative to hydrocarbons in drilling fluids.

Packaging

Drums of 180 kg net

IBCs of 900 kg net

Chemical and Physical Properties

Test Method		Unit	Typical	Specification
DIN 51757 (4)	Density, 20°C	kg/m ³	870	860-880
ISO 6271	Colour	APHA	5	max. 80
Visual	Appearance		Clear	Clear
ISO 3016	Pour point	°C	-90	-
ISO 2719	Flash point	°C	75	-
ISO 3104	Dynamic viscosity, 25°C	mPa·s	1.3	-

Safe Use and Handling

For specific safe use and handling information, or to obtain a ESTISOL 140 Material Safety Data Sheet, contact Esti Chem A/S.

Contact Us:

Esti Chem A/S
Erhvervsparken 16
DK-4621 Gadstrup
Denmark
Tel.: +45 56 653372
Fax: +45 56 653375
<http://www.estichem.com>
12/2012

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.